

## G63-P3047650

## Mini-pressostat G63-P3047650

These devices are pressostats with fixed regulations intended for the refrigeration.

Two models are available: G60 pressostats low-pressure and G63 pressostats high-pressure.

They are equipped with a relay SPDT with automatic rearmament or with a relay SPST in rearm textbook by button button.

Various types of connections are available: direct Connecting 1/4 " flare female, connecting by capillary with nut 1/4 " flare female.

A depressant Schraeder is incorporated in both cases.

### TECHNICAL DATA:

#### G60: low pressure

- Beach of functioning: - 0,35 in 7 Bars
- maximal Pressure of use: 20 Bars

#### G63: high pressure

- Beach of functioning: 7 in 31 Bars
- maximal Pressure of use: 35 Bars
- Difference: according to the regulation manufacture
- Compatible with all the not corrosive gases
- limit Temperatures with the electric connectors: - 3 / 55°C
- Maximum temperature in expulsion compressor: 135°C
- Temperatures of storage: - 30 / 70°C
- Be able to of cut of the contacts: 6A inductive in 250V
- Models with automatic rearmament: IP00 with opened connectors, IP44 with protective cover, IP66 with hood and disk of waterproofness
- Model with manual rearmament: IP44 with button opened button, IP66 with button protected button
- These devices were conceived in agreement with the European directives, UL and CSA(FRENCH BROADCASTING AUTHORITY).

